

EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	3561	(128/206.16,206.12,206.21,206.24,206.27,206.28,207.11,205.25 OR 24/30.55,30.51,336,572.1,573.1,581.1,578.1).ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	AND	ON	2006/09/26 12:46
L2	98	gunaratnam.in.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	AND	ON	2006/09/26 13:19
L3	72	kwok.in. near p	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	AND	ON	2006/09/26 13:20
S1	0	WO8701950.PN.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	AND	ON	2006/09/26 11:37
S2	0	WO-8701950.PN.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	AND	ON	2006/09/22 11:56
S3	1	WO-8701950-A1.PN.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	AND	ON	2006/09/22 11:57
S4	2	"5205832".pn.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	AND	ON	2006/09/22 12:01
S5	2	"6374826".pn.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	AND	ON	2006/09/22 12:01
S6	2	"6374826".pn.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	AND	ON	2006/09/25 16:00

EAST Search History

S7	1	"10090173".ap.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	AND	ON	2006/09/26 11:38
S8	3	"10090173"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	AND	ON	2006/09/26 11:38



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification⁴ : A62B 18/02</p>	<p>A1</p>	<p>(11) International Publication Number: WO 87/ 01950 (43) International Publication Date: 9 April 1987 (09.04.87)</p>
<p>(21) International Application Number: PCT/GB86/00576 (22) International Filing Date: 26 September 1986 (26.09.86) (31) Priority Application Number: 8523795 (32) Priority Date: 26 September 1985 (26.09.85) (33) Priority Country: GB (71) Applicant (for all designated States except US): PRO-TECTOR SAFETY LIMITED [GB/GB]; Great George Street, Wigan, Greater Manchester WN3 4DE (GB). (72) Inventor; and (75) Inventor/Applicant (for US only) : FEENEY, John, Robert [GB/GB]; Protector Safety Limited, Great George Street, Wigan, Greater Manchester WN3 4DE (GB).</p>		<p>(74) Agent: ATKINSON, Peter, Birch; Marks & Clerk, Suite 301, Sunlight House, Quay Street, Manchester M3 3JY (GB). (81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BG, BR, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CM (OAPI patent), DE, DE (European patent), DK, FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL, NL (European patent), NO, RO, SD, SE, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent), US. Published <i>With international search report.</i></p>
<p>(54) Title: RESPIRATOR</p> <div data-bbox="373 1155 1218 1806"> </div> <p>(57) Abstract</p> <p>A respirator having a cup-like body (7) associated with an air inlet (8) and an air outlet (9) and having a peripheral sealing element (2) shaped for location across the nose and around the mouth of a wearer wherein the sealing element (2) is located in position by a clamping element (3) which is releasably secured to the cup-like body (7).</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	ML	Mali
AU	Australia	GA	Gabon	MR	Mauritania
BB	Barbados	GB	United Kingdom	MW	Malawi
BE	Belgium	HU	Hungary	NL	Netherlands
BG	Bulgaria	IT	Italy	NO	Norway
BJ	Benin	JP	Japan	RO	Romania
BR	Brazil	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	LI	Liechtenstein	SN	Senegal
CH	Switzerland	LK	Sri Lanka	SU	Soviet Union
CM	Cameroon	LU	Luxembourg	TD	Chad
DE	Germany, Federal Republic of	MC	Monaco	TG	Togo
DK	Denmark	MG	Madagascar	US	United States of America
FI	Finland				

- 1 -

RESPIRATOR

The present invention relates to a respirator and more particularly (but not exclusively) to those
5 respirators known as half-mask respirators which are intended to cover only the nose and mouth of a wearer.

Most conventional half-mask respirators are moulded from natural rubber or other similar material (synthetic rubber, silicone rubber, PVC etc.).
10 With this type of mask the face seal is effected by the part of the mask in contact with the face. To achieve this it is usual to have a reflex edge in which region the moulding is thinner and more flexible.

15 Other masks use an inflatable seal against the face and this may be combined with a rubber mask or a rigid plastic mask.

With the conventional masks, it may not be possible to replace the seal easily once it has lost
20 its effectiveness due to repeated use of the mask which must therefore be discarded.

It is an object of the present invention to obviate or mitigate the above disadvantage.

According to the present invention there is
25 provided a respirator having a cup-like body associated with an air inlet and an air outlet and having a peripheral sealing element shaped for location across the nose and around the mouth of a wearer, wherein the sealing element is located in
30 position by a clamping element which is releasably secured on the cup-like body.

Preferably, the cup-like body and clamping
element each have flanges which come into
face-to-face clamping relationship when the clamping
35 element is mounted on the body, and the seal has a

- 2 -

skirt or the like which is clamped between these flanges to retain the seal in position.

The invention will be further described by way of example only with reference to the accompanying drawings in which:

Fig. 1 is an exploded perspective view of one embodiment of half-mask respirator in accordance with the invention;

Fig. 2 is an exploded, part-sectional side view of the mask shown in Fig. 1, but omitting details of the harness; and

Fig. 3 is a side view of the assembled mask.

The illustrated half-mask respirator comprises a cup-like body 1 shaped for location over the nose and mouth of a user, a cushion-like face seal 2 for location on the cup 1, an outer clamping element 3, a standard filter cartridge 4, an inhalation valve 18 (not shown in Fig. 1, but clearly illustrated in Fig. 2), exhalation valves 5 (only one shown), and harness straps 6.

Cup 1 is a rigid plastic moulding formed as a cup-shaped body 7 having an aperture 8 in a flat frontal face thereof and two apertures 9 in a flat basal face thereof. Aperture 8 is extended inwardly by an internally screw-threaded tubular projection 8a in which an air inlet valve 18 (see Fig. 2) is located. Projecting laterally from the rim of the body 7 is an integral flange 10.

Clamping element 3 is also a rigid plastics moulding and comprises a wall 11 with a stand-off guard portion 12. More particularly, wall 11 is shaped to be a close fit around the body 7 save that the guard portion 12 will stand slightly clear of the flat basal face of body 7 to allow the exhaust valves 5 to be positioned in apertures 9. The basal surface

- 3 -

of guard portion 12 is slotted so as to allow passage of air from valves 5.

Also provided on clamping element 3 is a flange 13 integral with the wall 11. Finally, stud-like projections 14 are provided on wall 11.

Complimentary snap-fit formations (not shown) are provided on the wall 11 of clamping element 3 and on the body 7 of cup 1 whereby clamping element 3 is a snap fit on cup 1. The snap fit formations may take a number of forms. For example, the cup-like body 7 may have a continuous or discontinuous undercut in which a complimentary projection on the inner surface of wall 11 locates. With element 3 snap-fitted on cup 1, the flanges 10 and 13 are in face-to-face clamping relation.

Face seal 2 is of the form illustrated in Fig. 1. More particularly the ring is shaped for location on, and around, the flange 10 of cup 1. Seal 2 is formed of a core ring of soft foam-rubber 15 clad with flexible PVC 16, such that seal 2 is of cushion-like construction. This PVC cladding 16 has a skirt 17 (the purpose of which will be described) provided around the inner periphery of the ring-like face seal body and extending inwardly thereof. The width of skirt 17 is substantially the same as that of flanges 10 and 13.

Assembly of the half-mask is as follows, it being assumed that inlet valve 18 and outlet valves 5 have been located in position.

Firstly, face-seal 2 is mounted on the cup 1 by manipulating the skirt 17 of seal 2 such that it overlies flange 10 of cup-like body 1. With the seal 2 so mounted on cup 1, a substantial part of the seal's ring like body is located on the side of flange 10 remote from the cup-shaped body 7.

- 4 -

Next, clamping element 3 is snap-fitted onto cup 1 thus ensuring that skirt 17 is securely clamped between flanges 10 and 13 thereby fixing seal 2 in position. With clamping element 3 located in position, guard portion 12 serves to protect valves 5 whilst allowing passage of air from the valves 5.

Assembly is completed by screwing cartridge 4 into projection 8a and finally attaching harness straps 6 to studs 14.

The assembled mask is of course worn with the seal 2 locating over the bridge of the nose and around the mouth of a wearer, the mask being supported in position by the harness straps 6 locating around the back of the wearers head. When the mask is worn, these harness straps 6 'pull' the clamping element 3 towards the face of the wearer thus enhancing the clamping action.

During inhalation, air is drawn through (and thus filtered by) the cartridge 4. Exhaled air is exhausted via the outlet valves 5.

It is inevitable that seal 2 will lose its effectiveness after repeated usage of the mask. With the illustrated mask construction, the seal may be replaced quickly and easily by releasing and removing clamping element 3 from cup 1 (after removal of cartridge 4 if necessary), removing the old seal, fitting a new one, and re-assembling the mask. Consequently there is no need to dispose of the mask once the seal loses its effectiveness.

The illustrated mask has a cushion-like seal. Other types of seal could however be used, e.g. inflatable seals or reflex-edge seals.

- 5 -

CLAIMS:

1. A respirator having a cup-like body associated with an air inlet and an air outlet and having a peripheral sealing element shaped for location across the nose and around the mouth of a wearer wherein the sealing element is located in position by a clamping element which is releasably secured to the cup-like body.
2. A respirator as claimed in claim 1 wherein the cup like body has a cup for location over the mouth and across the nose of a wearer and a first flange extending around the periphery of the cup said clamping element locates around the cup and has a second flange, and a portion of said sealing element is clamped between said first and second flanges.
3. A respirator as claimed in claim 2 wherein the cup has a front face having an aperture therein, said aperture being extended by an inwardly directed tubular projection forming the air inlet and in which is provided an inhalation valve.
4. A respirator as claimed in claim 3 wherein a filter cartridge is supported in said tubular projection.
5. A respirator as claimed in claim 2 wherein the cup has a flat basal surface having at least one aperture in which is located an exhalation valve.
6. A respirator as claimed in claim 5 wherein the clamping element has a guard portion for protecting the exhalation valve.
7. A respirator as claimed in any one of claims 1 to 6 wherein the clamping element and the cup like body have complimentary snap fit formations for effecting said releasable securement.
8. A respirator as claimed in any one of claims

- 6 -

1 to 7 wherein the sealing element comprising a ring of soft foam rubber clad with a flexible plastics material.

5 9. A respirator as claimed in claim 8 wherein the flexible plastics material is PVC.

10 10. A respirator as claimed in any one of claims 1 to 9 wherein the clamping element is provided with studs for the securement thereto of a harness for location around the back of the head of a wearer of the mask.


15

20


25

30

35




SUBSTITUTE SHEET



SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International Application No PCT/GB 86/00576

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁴		
According to International Patent Classification (IPC) or to both National Classification and IPC		
IPC ⁴ : A 62 B 18/02		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
IPC ⁴	A 62 B	
Documentation Searched other than Minimum Documentation to the extent that such Documents are included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ⁶	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
X,Y	DE, C, 207751 (WESTFALIA A.G.) 27 July 1907, see page 1; figures 1,2 --	1,2,3-7
Y	US, A, 2823671 (GARELICK, J.J.) 18 February 1958, see column 2, line 23 - column 3, line 46; figures 1,5 --	1-7
A	US, A, 2931356 (SCHWARZ, K.H.) 5 April 1960, see column 3, lines 10-34; figures 3,4 --	1,8
A	US, A, 3545436 (HOLLOWAY, R.L.) 8 December 1970 --	
A	DE, C, 334138 (DRAEGER, A.B.) 9 March 1921 --	
A	DE, C, 702315 (AUERGESELLSCHAFT) 22 January 1936 -----	
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>¹⁰ Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p> </div> </div>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search		Date of Mailing of this International Search Report
10th December 1986		22 JAN 1987
International Searching Authority EUROPEAN PATENT OFFICE		Signature of Authorized Officer M. VAN MOL 

Form PCT/ISA/210 (second sheet) (January 1985)

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON

INTERNATIONAL APPLICATION NO. PCT/GB 86/00576 (SA 14685)

This Annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 18/12/86

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-C- 207751		None	
US-A- 2823671		None	
US-A- 2931356		None	
US-A- 3545436	08/12/70	None	
DE-C- 334138		None	
DE-C- 702315		None	

For more details about this annex :
see Official Journal of the European Patent Office, No. 12/82